



OFFICE OF THE MISSION DIRECTOR  
NATIONAL HEALTH MISSION, ASSAM  
SAIKIA COMMERCIAL COMPLEX, CHRISTAN BASTI, G.S ROAD, GUWAHATI-781005  
PH.NO : 0361-2363062 ; TELE FAX : 0361-2363058

Website: [www.nrhmassam.in](http://www.nrhmassam.in)

e-mail: [misnrhm.assam@gmail.com](mailto:misnrhm.assam@gmail.com)

No: **NHM/PROC/HOSP-FURNITURE/3100/2016-17/22297**

Date: **18/03/2017**

### **CORRIGENDUM NO.2**

#### **e-TENDER FOR ENTERING INTO RATE CONTRACT FOR HOSPITAL & OFFICE FURNITURE**

This has reference to the e-tender No: **NHM/PROC/HOSP-FURNITURE/3100/2016-17/ 18136** Date: **09/01/2017** & Corrigendum No: **NHM/PROC/HOSP-FURNITURE/3100/2016-17/21792** Date: **14/3/17** for entering into rate contract for supply & installation of Hospital and Office Furniture. The following amendment may be taken note of prior to submission of Bids.

1. Manufacturer/ Manufacturers whose products have been quoted should have valid **CE/USFDA Certificate** *instead of EuCE/USFDA Certificate* in addition to valid ISO 9001:2008, ISO 13485: 2003, OHSAS 18001:2007, ISO 14001:2004 certificates etc. as specified at Annexure XII (Rev-2) of this Corrigendum.
2. **Annexure XI "CHECK LIST" is amended be read as follows:**

#### **ANNEXURE-XI (Rev-2)**

#### **CHECK LIST**

Sl.	Cover A	Must be uploaded particulars	Yes	No
1.	Court Fee Stamp/IPO & Tender Document Fee furnished	Must be uploaded		
2.	EMD in the form of DD/BG furnished	Must be uploaded		
3.	Documentary evidence for the Constitution of the company			
4.	Duly attested / notarized copy of Manufacturing License issued by the competent Licensing Authority for the products quoted			
5.	Attested Photocopy of IEC if any			
6.	The instruments such as Power of Attorney, Resolution of Board etc.			
7.	Undertaking as per Annexure I A and I B	Must be uploaded		
8.	Manufacturer's Authorization as per Annexure II	Must be uploaded		
9.	ISO 9001:2008, ISO 13485: 2003, CE/USFDA, OHSAS 18001:2007, ISO 14001:2004 certificates as specified in Annexure XII.	Must be uploaded		
10.	Annual Turnover Statement for 3 years (Annexure – III	Must be		

	A & Annexure –III B)	uploaded		
11.	Performance Statement as per Annexure IV and copy of single value order	Must be uploaded		
12.	Sales Tax Clearance Certificate as Annexure V			
13.	Undertaking for Embossment of logo as per Annexure VI			
14.	Details of Manufacturing Unit as per Annexure VII			
15.	List of items quoted with name of Manufacturer as per Annexure VIII	Must be uploaded		
16.	Undertaking on Fraud & Corruption as per Annexure IX			
17.	Agreed Terms & Conditions as per Annexure- X			
18.	Technical Cum Compliance Specification Sheet as per Annexure XII (Rev-2)	Must be uploaded		
19.	Price Bid as BOQ (as e.g. set in Annexure XIII) to be uploaded online only. Hardcopy of the same will not be accepted.	Must be uploaded		

**3. Annexure XII “Technical cum Compliance Specification Sheet” is amended to be read as follows:**

**ANNEXURE XII (Rev-2)**

**Technical cum Compliance Specification Sheet: (TO BE SUBMITTED BY THE MANUFACTURER)**

Sl.No	Tender Specification	Technical Specification Quoted by the bidder	Deviation if any
1	<p><b><u>Patient's Examination Couch with Foot Step (Single):-</u></b></p> <p>Overall approx. size should be 1830mm L x 550mm W x 820mm H. minimum  Fixed upholstered top 50mm thick in two sections.  Body frame work should be made from 20G CRCA sheet.  Couch should be fitted with mild steel legs.  Headrest adjustable by gas spring.  Upper section of box approx. size 1200mm L x 450 mm W x 610mm H with three sliding drawers with separate doors.  Sliding foot step under the front side of lower middle cabinet.  B.P. apparatus tray made of 18G MS sheet of approx. size 350 mm L x 120mm W x 20mm H provided on a swinging rod rotating through a bush fixed on the body of the couch.</p>		

	<p>Supplied with Single Foot Step. All MS parts should be pre-treated in Seven Tank &amp; Powder Coated.</p> <p>Should be CE/US FDA, OHSAS 18001:2007, ISO 9001:2008, ISO 13485:2003, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b>Warranty for 2yrs</b></p>		
2	<p><b><u>Revolving Stool :-</u></b></p> <p>Overall all height adjustable Approx. Size: 480mm to 670mm H Tubular four legs base of 25.4 x 18g ERW tube. 300mm MS dia SS Top Height adjustment by screw mechanism. The legs should be fitted with high quality PVC shoes with nylon reinforcement. All MS Parts should be 7 tanks Pre-treated &amp; powder coated &amp; SS parts finished with glossy polish. Minimum 30 mm Cushioned top with waterproof rexine cover.</p> <p>Should be CE/US FDA, OHSAS 18001:2007, ISO 9001:2008, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b>Warranty for 2yrs</b></p>		
3	<p><b><u>Doctor's Table :-</u></b></p> <p>Size :1200 X 750 X 750 BEECH with 2 drawer hanging unit, Size: 400 X 400 X 300, Table Top: Table tops made of 25mm (minimum) Pre-laminated particle board of E-1 Grade Conforming to IS: 12823 of desired color with PVC edge banding. All exposed edge sealed by 2mm (minimum) thick PVC Imported edge Banding. Table Top Support: 18 mm thick PLB gable ends &amp; 18 modesty Panel</p> <p><b>Warranty for 2yrs</b></p> <p>Should be OHSAS 18001:2007, ISO 9001:2008, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p>		
4	<p><b><u>Doctor's Chair :-</u></b></p> <ul style="list-style-type: none"> <li>· Cushioned seat and back.</li> <li>· Pneumatic height adjustable.</li> </ul>		

	<ul style="list-style-type: none"> <li>· Height adjustable and swinging back rest</li> <li>· 5 legs chrome plated base with foot ring</li> </ul> <p>Base fitted with 50 mm dia castors</p> <p><b>Warranty for 2yrs</b></p> <p>Should be OHSAS 18001:2007, ISO 9001:2008, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p>		
5	<p><b><u>Visitor's Chair :-</u></b></p> <p>The frame is made out of 25mm thick tube Thermo set powder coating by epoxy polyester hybrids to a thickness of 40 – 50 microns after 7 step pre-treatment processes.</p> <p>Seat: Made of 12mm thick plywood cushioned with 37mm thick PU foam of density 32.</p> <p>Back: Made of 10mm thick plywood, cushioned with 25mm thick PU foam of density 26.</p> <p>Fabric: Colour from fabric shade card</p> <p>Dimensions:</p> <p>Seat Width: 440mm, Seat Height: 460mm &amp; Seat Depth: 425mm</p> <p>Overall Height: 810mm &amp; Overall Width: 550mm</p> <p><b>Warranty for 2yrs</b></p> <p>Should be OHSAS 18001:2007, ISO 9001:2008, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p>		
6	<p><b><u>Bed side screen-3 Fold:-</u></b></p> <p>Overall Size : 1680mm L x 2450mm W</p> <p>Tubular frame work should be made from 19mm dia x 1.2mm ERW CRCA tubes.</p> <p>Legs Base should be made from dia 25.4mm x 1.2mm tube ERW CRCA Tubes Fitted with 50mm dia non-rusting castor. Middle panel should be 1220mm and side panels 610mm each side. Should have curtain hooks and wire.</p> <p>Should be OHSAS 18001:2007, ISO 9001:2008, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b>Warranty for 2yrs</b></p>		

7	<p><b><u>Invalid Wheel Chair:-</u></b></p> <p>Should be Folding type, made of mild steel tubular construction OD 22 mm.  With fixed arm rest and fixed aluminum foot rests with folding action.  Seat and back rest should be of superior quality leatherite. Safety belt should be available for holding the patient.  Two rear solid rubber typed bicycle wheel, dia 24 inch with Self propelling hoops fitted with hand brakes. Two front swivel castor of 200mm chrome-plated finish.</p> <p>Should be CE/USFDA, OHSAS 18001:2007, ISO 9001:2008, ISO 13485:2003, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p style="text-align: center;"><b><i>Warranty for 2yrs</i></b></p>		
8	<p><b><u>Stretcher-on-trolley:-</u></b></p> <p>Made fully of SS 304 grade. Overall approx size: 2130mm L x 560mm W x 810mm H. Frame work should be made of ERW SS tubes welded with vertical upright of 31.75 mm OD x 18G SS tubes, reinforced at bottom with 35mm OD x 18G for fitting 150mm dia swivels castors wheels, all without brake. All horizontal stays should be made of 25.4mm OD x 18G SS tube. Stretcher made of 20 G SS sheet dished in the middle &amp; supported horizontally on 25.4mm OD x 18G SS tubes. Three additional 25 x 5mm SS flat supports welded to support. MS sheet top from underneath widthwise. Pushing handle at both ends shall be made of 25.4 mm x 18G SS tube. Four stump legs of 25.4mm x 18G ERW SS tube should be welded at the bottom of the stretcher frame. Should be fitted with PVC or synthetic material having Nylon reinforced. Safety belt should be available for holding the patient.</p> <p>Should be CE/USFDA OHSAS 18001:2007, ISO 9001:2008, ISO 13485:2003, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years</p>		

	(2013-14, 2014-15 & 2015-16) also.  <b>Warranty for 2yrs</b>												
9	<p><b><u>Patient Waiting Chair (3-seater):-</u></b>  Waiting area chairs  Ergonomically designed seat/back  Twin tube designer under structure  Waterfall seat edge With/ without arms</p> <table border="1"> <thead> <tr> <th>Dimensions</th> <th>Width</th> <th>Depth</th> <th>Height</th> <th>Seat height</th> </tr> </thead> <tbody> <tr> <td>3 Seater</td> <td>152cm</td> <td>46cm</td> <td>85cm</td> <td>46cm</td> </tr> </tbody> </table> <p>Should be OHSAS 18001:2007, ISO 9001:2008, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b>Warranty for 2yrs</b></p>	Dimensions	Width	Depth	Height	Seat height	3 Seater	152cm	46cm	85cm	46cm		
Dimensions	Width	Depth	Height	Seat height									
3 Seater	152cm	46cm	85cm	46cm									
10	<p><b><u>Medicine Rack :-</u></b>  Double faced Slotted Angle Iron Racks with Adjustable 5 shelves double faced with 4 compartments covered from two by slotted angle. All the components should have final finish of powder coating with dry film thickness on minimum 50 microns with prior anti rust treatment in multi-colour shade including nut, bolt, corner, etc. complete.</p> <p><b><u>Specification for Raw Materials:</u></b>  (i) Cold Rolled (CR) sheets of steel conforming to IS 513 /10748. (ii) The Stanchion: - 2mm thick (iii) The Shelf: - 0.80 mm thick (iv) The Shoe: 3.15mm thick (conforming to IS 10748) (v) Shelf and Shelf Brackets: Capable of taking a load of 70 kgs.  Dimension 900mm x 380mm x 1800mm.  Should be OHSAS 18001:2007, ISO 9001:2008, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b>Warranty for 2yrs</b></p>												
11	<p><b><u>Almirah for Medicines :-</u></b>  Should be Epoxy Powder coated.  Should be made of heavy MS Sheet all three sides as well as front door.  Shelves removable. Door with lock &amp; key.  Dimension:912mmX482mmX1850mm±5mm  Should be OHSAS 18001:2007, ISO 9001:2008, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b>Warranty for 2yrs</b></p>												

12	<p><b><u>Office Table :-</u></b></p> <p>Size :1200 X 600 X 750 BEECH with 2 drawer hanging unit  Size: 400 X 400 X 300  Table Top: Table tops should be made of 25mm (minimum) Pre-laminated particle board of E-1 Grade of desired color with PVC edge banding. All exposed edge should be sealed by 2mm (minimum) thick PVC Imported edge Banding.  Table Top Support: 18 mm thick PLB gable ends &amp; 18 modesty Panel</p> <p>Should be OHSAS 18001:2007, ISO 9001:2008, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b><i>Warranty for 2yrs</i></b></p>		
13	<p><b><u>Office Chair :-</u></b></p> <p>Nylon base with glass filled Nylon castors gas lift with 100mm travel. Synchronic Tilt Mechanism with Single Position Lock  Should be Thermo set powder coating by epoxy polyester hybrids.  Seat should be made out of 4mm &amp; 15mm molded hot pressed plywood cushioned with high-density pre-molded foam of 55 – 60 density. Back is to be made out of mesh back fabric.  Arms – High density height adjustable cushioned polyurethane – padded arms.</p> <p><b><u>Dimensions:</u></b>  Chair Height – 900mm to 1000mm, Chair Width – 600mm (Center arm to arm), Seat Height 400mm to 500mm, Arm Height 190mm to 290mm &amp; Seat Depth 550mm</p> <p>Should be OHSAS 18001:2007, ISO 9001:2008, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b><i>Warranty for 2yrs</i></b></p>		
14	<p><b><u>Instrument Cabinet. :-</u></b></p> <p>Compact cabinet should be made of 3 sides close MS Sheet having polycarbonate door panel in the front.  Five adjustable 6.0mm polycarbonate shelves &amp; front lockable door with 4mm polycarbonate panel</p>		

	<p>Pre-treated and oven baked finish  Size : (H) 63" x (B) 24" X (D) 18"  Should be ISO 9001:2008 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b>Warranty for 2yrs</b></p>		
15	<p><b>IV Stand:-</b>  Made of 304 Grade SS pipes,  Moulded five-spiked base on 50 mm castors,  304 Grade SS adjustable rod with double hook.</p> <p>Should be CE/US FDA, ISO 9001:2008, ISO 13485:2003, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b>Warranty for 2yrs</b></p>		
16	<p><b>Dressing Trolley:-</b>  Should be made from SS 16SWG pipes having two SS Machine pressed dipped tops provided with four-side side railing, holder cage for bowl and bucket, SS bowl and bucket, push handle, on 10cms castors.  Dimension: 76 L x 46 W x 81 H cms.</p> <p>Should be CE/US FDA, ISO 9001:2008, ISO 13485:2003, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b>Warranty for 2yrs</b></p>		
17	<p><b>Hospital Bed with Mattress :-</b>  Frame should be made of rectangular 16 G CRCA pipes, 18 G CRCA perforated sheet top, SS head and foot bows should be fitted with laminated wooden boards, provided with mattress guard, provision for fixing IV/Saline rod, pre-treated in 7 Tank hot processes and powder coated. Dimension: 203 L x 90 W x 60 H cms. 4" Supplied with 4" PU Foam Mattress covered with water proof rexine.</p> <p><b>Specifications of mattress:-</b>  Single section Mattress with 4" thick PU Foam of 32 densities covered with PVC Rexine.</p> <p>Mattress of the bed is made up of foam with</p>		



	<p>anti-microbial agent incorporated into all components for prohibiting growth of bacteria and fungi. Sealed stitches and water proof zip. <b>Standard Accessories:</b> Mosquito net poles set. Warranty: 02 years</p> <p>Should be CE/US FDA, OHSAS 18001:2007, ISO 9001:2008, ISO 13485:2003, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2012-13, 2013-14 &amp; 2015-16) also.</p> <p><b>Warranty for 2yrs</b></p>		
18	<p><b>ICU Bed. :-</b></p> <p>Frame made of 16 G CRCA rectangular pipes, 18G CRCA sheet four section perforated top with back-rest, knee-rest, Trendelen-burg's and reverse Trendelen-burg's position, Hi-Lo (high-low) height adjustable (positions maneuverable by four separate screw mechanisms) imported ABS panels/head and leg bows, Aluminium Collapsible Side Rails, provided with one number IV/saline rod with provision for fixing IV/saline rod at four corners of the bed frame, 15 cms diameter swiveling castors which two with brakes. The bed is pre-treated in 7 tank hot process and powder coated. Dimension 203L x 90Wx 60-80 H Cms (approx.).</p> <p><b>Specifications of mattress:-</b> Multi section Mattress with 4" thick PU Foam of 32 densities covered with PVC Rexine. Mattress of the bed is made up of foam with anti-microbial agent incorporated into all components for prohibiting growth of bacteria and fungi. Sealed stitches and water proof zip.</p> <p>Should be CE/US FDA, OHSAS 18001:2007, ISO 9001:2008, ISO 13485:2003, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p>Mattresses of the ICU bed should be as per standard specification.</p> <p><b>Warranty for 2yrs</b></p>		
19	<p><b>Fowler Bed:-</b></p> <p>Frame made of 16 G CRCA rectangular pipes,</p>		

	<p>18G CRCA sheet four section perforated top with back-rest, knee-rest maneuverable from foot-end by separate screws, imported ABS panels/head and leg bows, provision for fixing IV/saline rod at four corners of the bed frame, provided with mattress guard at four locations, the rod mounted on 10 cms diameter swiveling castors which two with brakes. The bed pre-treated in 7 tank hot process and powder coated. Dimension: 203 L x 90 W x 60 H cms (Approx.).</p> <p><u>Specifications of mattress:-</u></p> <p>Multi section Mattress with 4” thick PU Foam of 32 densities covered with PVC Rexine. Mattress of the bed is made up of foam with anti-microbial agent incorporated into all components for prohibiting growth of bacteria and fungi.</p> <p>Sealed stitches and water proof zip.</p> <p>Should be CE/ US FDA, OHSAS 18001:2007, ISO 9001:2008, ISO 13485:2003, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b>Warranty for 2yrs</b></p>		
20	<p><b>Semi-Fowler Bed:-</b></p> <p>Frame made of 16G CRCA rectangular pipes, 18G CRCA sheet two section perforated top with back-rest maneuverable from foot-end by screw, imported PM/ABS panels/head &amp; Foot Bows, bed mounted on rubber stumps, provided with mattress guard on four locations, provision for fixing IV/Saline rod. The bed pre-treated in 7 tank hot process and powder coated. Dimension: 203L x 90 W x 60 H cms (Approx.).</p> <p><u>Specifications of mattress:-</u></p> <p>Multi section Mattress with 4” thick PU Foam of 32 densities covered with PVC Rexine. Mattress of the bed is made up of foam with anti-microbial agent incorporated into all components for prohibiting growth of bacteria and fungi. Sealed stitches and water proof zip.</p> <p>Should be CE/US FDA, OHSAS 18001:2007, ISO</p>		

	<p>9001:2008, ISO 13485:2003, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p style="text-align: center;"><b>Warranty for 2yrs</b></p>		
21	<p><b>Bed Side Locker:-</b></p> <p>Approximate dimension: 16" L x 16" W x 32" H.</p> <p>Should be made of 20 G MS CRCA Sheet.</p> <p>Should be Joint less SS top with 3 sides raise edges.</p> <p>Should have one storage cabinet and one drawer under the top and space for keeping utilities between the drawer and cabinet.</p> <p>Legs should be fitted with 2 non-rusting castors of 50mm dia and 2 PVC Stumps on front side.</p> <p>2 Rubber / PVC Buffer should be provided at rear side of the locker.</p> <p>Pre-treated in seven Tank and Epoxy Powder Coated.</p> <p>Should be CE/ US FDA, OHSAS 18001:2007, ISO 9001:2008, ISO 13485:2003, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p style="text-align: center;"><b>Warranty for 2yrs</b></p>		
22	<p><b>Foot Step Double:-</b></p> <p>Overall Approx. size: 510mm L X 300mm W x 230/450 H</p> <p>First Step height should be 230mm approx.&amp; second step size 450mm approx. step should be made of 18G CRCA sheet. Welded on MS.</p> <p>Tubular frame of 25.4mm x 18G fitted with aluminum treated flats of size: 500mm L x 32mm W x 3 mm thick, fitted by aluminum pop rivet. The legs should be fitted with high quality PVC shoes with nylon reinforcement.</p> <p>All MS parts should be 7 tank pretreated &amp; powder coated.</p> <p>Should be CE/USFDA, OHSAS 18001:2007, ISO 9001:2008, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p style="text-align: center;"><b>Warranty for 2yrs</b></p>		

23	<p><b><u>Mayo's Instrument Trolley. :-</u></b></p> <p>Overall Approx. Tray Size: 560L x 400W mm  Should be Adjustable height of tray Approx. 760 x 1270mm through gear handle  Frame work should be made of 50 x 30 x 1.22 mm rectangular M.S. Tubes.  Vertical Tube should be made of 50 mm x 50 mm x 1.22mm MS Tubes.  Tray should be made of 0.9mm thick S.S. 304 Grade sheet.  Tray frame should be made of 9mm SS Rod  Trolley should be mounted on 50mm dia non-rusting castors  MS Parts should be pre-treated in 7 tanks and powder coated.</p> <p>Should be CE/USFDA, ISO 9001:2008, ISO 13485:2003 ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b><i>Warranty for 2yrs</i></b></p>		
24	<p><b><u>Instrument Trolley. :-</u></b></p> <p>Should be made of SS 16 SWG pipes/ 20 SWG two shelves, provided with three-side side railing on top, having four side-railing on bottom self, on 7.5cms castors.  Dimension: 60L x 46W x 81H cm.</p> <p>Should be ISO 9001:2008, ISO 13485:2003, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b><i>Warranty for 2yrs</i></b></p>		
25	<p><b><u>Labour Table :-</u></b></p> <p>Overall Approx. Max. Size 72" x 27" x 30"  Frame work should be made of 31mm x 18G and supporting tubes made of 25mm x 18G S.S. Tube  Leg should be fitted with PVC Stamps.  Should be made of full stainless steel.  Back rest section should be adjustable on ratchet mechanism.  Leg end section should be slide under the main section by smooth mechanism  The entire table top gives trendlenburg position by screw system.  Should have Height adjustable a pair of leg holders with straps.  Complete with self-locking traction handle at</p>		

	<p>side, SS IV Rod and foam mattress. Should be CE/ US FDA, OHSAS 18001:2007, ISO 9001:2008, ISO 13485:2003, ISO 14001:2004 certificates. All such certificates should have been held by the manufacturer in the past three years (2013-14, 2014-15 &amp; 2015-16) also.</p> <p><b><i>Warranty for 2yrs</i></b></p>		
--	---	--	--

All other terms and conditions of the tender referred to above shall remain unchanged.

**Sd/-**  
**Mission Director, NHM, Assam**